

EC-Material Safety Datasheet according to 93/112 EEC & 91/155 EEC for the liquid

Trade name:

DC PRESS Inject Liquid

Issue:

A4 dated: 15.04.09

1. Identification of the substance / preparation and the company

Information on the product

Trade name: DC PRESS Inject Liquid

Use / Purpose: Denture Base Resin, self-curing acrylic, liquid component of the 2-component acrylic system based on methyl methacrylate (powder and liquid), for the purpose of crafting individual dentures.

Information on the manufacturer

DC Dental Central Großhandelsges.mbH

Carl-Zeiss-Str.2

D-22946 Trittau

Tel.: +49 (0)4154 / 84 37 - 0

Fax: +49 (0)4154 / 84 37 - 33

email: office@dental-central.de

2. Composition / Information on ingredients

Chemical characterization

Methyl methacrylate

Hazardous ingredients

Methyl methacrylate

concentration	60 to 100%
chemical formula	C ₅ H ₈ O ₂
CAS-Nr.	80-62-6
EG-Nr.	201-297-1
INDEX-Nr.	607-035-00-6
hazard symbols	F, Xi
R-phrases	11-37/38-43

3. Hazards identification

Hazard symbols



Highly flammable



Irritating

Special guidelines concerning dangers to humans and the environment

Highly flammable. Irritating to respiratory system and skin. May cause sensitization by skin contact.

4. First aid measures

General Information: Remove soaked clothing immediately. Medical treatment is necessary if symptoms occur that are obviously caused by skin or eye contact with the product or by inhalation of its vapours.

After inhalation: In case of inhalation remove casualty to fresh air and allow to rest. Seek medical advice.

After contact with skin: In case of contact with skin wash off immediately with soap and water. If skin irritation occurs, seek medical advice.

After contact with eyes: In case of contact with eyes rinse thoroughly with plenty of water while keeping the eyelids apart. If irritation persists seek medical advice.

After ingestion: Do not induce vomiting. Seek medical advice immediately.

Page 1

EC-Material Safety Datasheet according to 93/112 EEC & 91/155 EEC for the liquid

Trade name:

DC PRESS Inject Liquid

Issue:

A4 dated: 15.04.09

5. Fire-fighting measures

Suitable extinguishing media

Foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons

Water

Special protective equipment for fire fighting

Wear self-contained breathing apparatus

6. Accidental release measures

Personal precautionary measures

Assure appropriate air-flow. Wear protective clothing. Keep away sources of ignition. Use breathing apparatus if exposed to vapours/dust/mist/aerosol.

Environmental protection measures

Do not allow to get into drains/surface water/groundwater

Measures for cleaning

Large quantities: Remove mechanically (hydraulic pump). Assure explosion-safe measures!
smaller quantities: Pick up with liquid absorbing material (sand, diatomaceous earth, acid absorbent, sawdust or tissues)

7. Handling and storage

Instructions on safe handling

Keep container well closed. Assure appropriate air-flow.

Information on fire and explosion protection

Keep away from sources of ignition - no smoking. Take precautionary measures against static discharges. In the event of fire, cool the endangered containers with water.

Requirements for storage areas and containers

Storage temperature: +10 °C to +25 °C

Short term max.: - 20 °C to +30 °C

Store in original container only. Temperatures should never exceed 25 °C. Fill container up to 90% max, because enclosed oxygen (air) is needed for stabilization purposes. Keep out of direct sunlight. Special explosion safe environment needed to store quantities larger than 5l per container.

Additional Information

If the liquid should cool down to a temperature of lower than 10°C some of the ingredients may crystallize and sink to the bottom. If the materials temperature rises up to room temperature again these crystals dissolve again. The properties of the material will not be affected by this phenomena.

EC-Material Safety Datasheet according to 93/112 EEC &

91/155 EEC for the liquid

Trade name:

DC PRESS Inject Liquid

Issue:

A4 dated: 15.04.09

8. Exposure controls and personal protection

Components or products of decomposition according to point 10, with limit values related to the place of work which require monitoring.

LT-Value for

Methyl methacrylate	210 mg/m ³
CAS-Number	80-62-6
maximum limitation category	I

Remarks

Y: Danger of damage to unborn children is not to be expected as long as the LT-value does not exceed above mentioned amount.

General protective measures:

Do not inhale vapours. Avoid contact with eyes and skin.

Hygiene measures:

Keep working clothes away from regular clothing. Take off contaminated clothes immediately. Follow the regular standards of occupational hygiene. Clean skin thoroughly after work; apply skin cream.

Respiratory protection:

Breathing apparatus in case of high concentrations

Eye protection:

Wear protective goggles.

Body protection:

When handling larger quantities wear face shield, apron and chemical resistant boots.

Hand protection:

Wear protective gloves made of butyl rubber (0,7mm), break through time 300 min (EN 374). In practice, due to variable exposure conditions, this information can only be an aid to orientation for the selection of a suitable chemical protection glove. In particular, this information does not substitute suitability tests by the user.

general information:

Gloves should be changed regularly, especially after over excessive contact with the product. A different type of glove should be considered for each workplace.

9. Physical and chemical properties

Appearance

Form:	Liquid
Colour:	Colourless
Odour:	Ester-like, slightly sweet, stinging

EC-Material Safety Datasheet according to 93/112 EEC & 91/155 EEC for the liquid

Trade name:

DC PRESS Inject Liquid

Issue:

A4 dated: 15.04.09

Changes in physical state (related to the component methyl methacrylate)

Melting temperature:	-48,2 °C
Boiling temperature:	100,3 °C (at 1.013 hPa)
Flashpoint:	10 °C (DIN 51755)
Ignition temperature:	430 °C (DIN 51794)
Self ignition ability:	not determined
lower explosion limit:	1,7 %(V)
upper explosion limit:	12,5 % (V)
vapour pressure:	38,7 hPa (at 20 °C)
Density:	0,94 g/cm ³ (at 20 °C)
Relative vapor density related to air:	> 1 (at 20 °C)
solubility in water:	15,9 g/l (at 20 °C)
qualitative solubility:	miscible with most organic solvents
pH-value:	not applicable
n-octanol/water partition coefficient	log Pow 1,38 (measured)
dynamic viscosity:	0,63 mPa.s (at 20 °C, Brookfield)
further information	none

10. Stability and reactivity

Thermal decomposition:	No decomposition when used as directed.
hazardous reactions:	Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.
hazardous decomposition products:	None when used as directed.

11. Toxicological information

The following information is related to the component methyl methacrylate.

Acute oral toxicity:	>5.000 mg/kg; practically non-toxic if swallowed; LD50 rat, OECD 401
Acute inhalational toxicity:	29,8 mg/l; low toxicity by inhalation; LC50 rat, exposure 4h
Acute dermal toxicity:	>5.000 mg/kg; practically non-toxic in contact with skin; LD50 rabbit
Irritant effect on skin:	not irritating; rabbit; exposure 24h; FDA 1959 Draize, occlusive
Irritant effect on eyes:	not irritating; rabbit; Draize
Sensitization:	In sensitization tests on guinea pigs with and without adjuvant, both positive and negative results were found. In humans various types of allergic reactions have been observed (symptoms: headache, eye irritations, skin affections).
Toxicity on repeated administration:	NOAEL 25ppm; at said dosis no adverse effects were observed. At higher doses adverse effects were observed; rat; inhalative 2 a, 25-400ppm (Findings: damage to mucous membranes in the nose at 400ppm) NOAEL 2000ppm; rat; drinking water 2 a, 6-2000ppm (Findings: no toxic effects)
Mutagenicity:	Positive as well as negative results within in vitro mutagenicity / genotoxicity tests. No experimental indication of genotoxicity in vivo available. In summary not mutagenic according to internationally accepted criteria.

Page 4

EC-Material Safety Datasheet according to 93/112 EEC & 91/155 EEC for the liquid

Trade name:

DC PRESS Inject Liquid

Issue:

A4 dated: 15.04.09

Carcinogenicity: Non-carcinogenic in inhalation and feeding studies carried out on rats, mice and dogs.

Reprotoxicity / teratogenicity: No indications of toxic effects were observed in reproduction studies in animals.

Additional information: Avoid contact with the skin and eyes and inhalation of the product vapours.

12. Ecological information

Information on elimination (persistence and degradability)

Biodegradability: readily degradable, ca. 94 %
Method: OECD 301 C, 14d

Ecotoxicological effect

Fish toxicity (LC50): > 79 mg/l
Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96h

Daphnia toxicity (EC50): 69 mg/l
Daphnia magna, OECD 202, 48h

Algae toxicity (EC3): 37 mg/l
Scenedesmus quadricauda, DIN 38412 section 9, 8d

Algae toxicity (EC50) 170 mg/l
Selenastrum capricornutum, OECD 201, 96h

Bakteria toxicity (EC0) 100 mg/l
Pseudomonas putida

Additional ecological information

Do not allow to enter soil, waterways or waste water.

13. Disposal considerations

Product (Components, powder and liquid)

European waste code: **07 02 99**

Waste name: Not yet cured acrylic leftovers, compounds or components.

Recommendations: Must be disposed of in accordance with the regulations of the local authorities and the disposal company in a suitable and licensed facility.

Already cured acrylic leftovers (both components mixed and cured)

European waste code: **17 02 03**

Waste name: other cured acrylic waste

Recommendations: Can be disposed of in accordance with the regulations of the local authorities and the disposal company in a suitable and licensed facility.

Contaminated packaging

Recommendations: Can be burned in accordance with local regulations. Dispose decontaminated packaging at local recycling facilities.

EC-Material Safety Datasheet according to 93/112 EEC & 91/155 EEC for the liquid

Trade name:

DC PRESS Inject Liquid

Issue:

A4 dated: 15.04.09

14. Transport information

Overland transport

ADR/RID/GGVSE

Class: 3 flammable liquid
Dangerous cargo number: 339
UN Number: 1247
Packaging group: II
Label: 3
Declaration of the good UN 1247 Methyl methacrylate, Monomer, stabilized, 3, II



Inland waterway transport

ADNR

Class: 3 flammable liquid
UN Number: 1247
Packaging group: II
Label: 3
Declaration of the good UN 1247 Methyl methacrylate, Monomer, stabilized, 3, II



Shipment by sea

IMDG/GGVSee

Class: 3 Flammable liquid
UN Number 1247
EmS: F-E, S-D
Marine pollutant: -
Packing group: II
Proper Shipping Name: Methyl methacrylate, monomer, stabilized



Air transport

ICAO/IATA

Class: 3 Flammable liquid
UN Number 1247
Packing group: II
Proper Shipping Name: Methyl methacrylate, monomer, stabilized



DOT

UN 1247 Methyl methacrylate, monomer, stabilized

15. Regulations

Labelling in accordance to EC directive GefStoffV

requires labelling

Hazardous component for labelling

contains methyl methacrylate

Hazard symbols

F Highly flammable
Xi Irritant

Risk phrases (R-phrases)

11 Highly flammable
37/38 Irritating to respiratory system and skin
43 May cause sensitization by skin contact

EC-Material Safety Datasheet according to 93/112 EEC &

91/155 EEC for the liquid

Trade name:

DC PRESS Inject Liquid

Issue:

A4 dated: 15.04.09

Safety phrases (S-phrases)

- 24 Avoid contact with skin
- 37 Wear suitable gloves
- 46 If swallowed, seek medical advice immediately and show container or label

15. Regulations - continued -

National regulations (for Germany only)

- Technical regulation for air 5.2.5
- Water hazards class 1 (VwVwS, Annex 2)

Occupational restrictions

- Note for juveniles
- Note for pregnant women and nursing mothers

16. Other information

This product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is exceeded, the product may polymerize with heat evolution.

References

Relevant manuals and publications, toxicological and ecological studies of different manufacturers. (SIAR, OECD-SIDS, RTK public files)

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.